According to GB/T 16483-2008 and GB/T 17519-2013

Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022

SDS Record Number: CSSS-TCO-010-151567

Section 1 Chemical Product and Con	npany Identification
Chemical name:	Sea Foam High Mileage
Additional identification:	Not available
Product code:	HM16
Identification of the product:	See section 3
Relevant identified uses of the substance an	d uses advised against
Identified uses:	Fuel system treatment
Uses advised against:	Not available
Details of the supplier of the safety data shee	et
Name:	Sea Foam International, Inc.
Address:	812 Burlington Drive, Suite 100 Bismarck, ND USA 58504
Contact person(E-mail):	-
Telephone:	+1(701)751-7363
Fax:	-
Emergency telephone Number(24h):	National emergency contact for chemicals (agreement signed): 0532-83889090

Section 2 Hazards Identification

Precautionary statement Prevention:

Emergency Overview: Clear liquid with typical odor. Flammable liquid and vapor. May be ignited by open flame. Vapors are heavier than Air and collect in confined and low-lying areas. The product is insoluble and floats on water. The pressure in sealed containers can increase under the influence of heat. Hazardous combustion products: Carbon oxides; Nitrogen oxides (NOx); Sulphur oxides; Other unidentified organic compounds; irritating fumes and smoke. Causes serious eye irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

GHS Classification:		
Physical hazards	Flammable liquid	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity - single exposure	Category 3
	Aspiration toxicity	Category 1
Environmental hazards	Not classified	
Label elements		
Pictogram:		
Signal Word(s):	Danger	
Hazard Statement:	Flammable liquid and vapour.	
	Causes serious eye irritation.	
	May cause drowsiness and dizziness.	
	May be fatal if swallowed and enters airways.	

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment.

According to GB/T 16483-2008 and GB/T 17519-2013

Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022

Revision date: 20/06/2022	SDS Record Number: CSSS-TCO-010-151567
	Use non-sparking tools.
	Take action to prevent static discharges.
	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wash hands thoroughly after handling.
	Use only outdoors or in a well-ventilated area.
	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	IF SWALLOWED: Immediately call a POISON CENTER/doctor/
	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	IF INHALED: remove person to fresh air and keep comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	Call a POISON CENTER/doctor/ if you feel unwell.
	DO NOT induce vomiting.
	If eye irritation persists: Get medical advice/attention.
	In case of fire: Use dry chemical, foam, carbon dioxide and water fog to
	extinguish.
Storage:	Store in a well-ventilated place. Keep cool.
-	Store in a well-ventilated place. keep container tightly closed.
	Store locked up.
Disposal:	Dispose of contents/container in accordance with
·	local/regional/national/international regulations.
Physical and chemical hazards:	Flammable liquid and vapor. May be ignited by open flame. Vapors are heavier
,	than Air and collect in confined and low-lying areas. The product is insoluble and
	floats on water. The pressure in sealed containers can increase under the
	influence of heat. Hazardous combustion products: Carbon oxides; Nitrogen
	oxides (NOx); Sulphur oxides; Other unidentified organic compounds; irritating
	fumes and smoke.
Health Hazards:	Causes serious eye irritation. May cause drowsiness and dizziness. May be fatal
	if swallowed and enters airways.
Environmental hazards:	The product has no obvious harm to the water environment.
Other hazards:	No.

Section 3 Composition Information on Ingredients

Substance/Mixture/Article:

Ingredient(s):

Mixture

Chemical NameCAS No.Concentration (%)Hydrocarbon blendN/A< 95%</td>Isopropanol67-63-0< 25%</td>

Undisclosed ingredients include: 1) non-hazard ingredients, and 2) ingredients which are below the cut-off value required by Section 3.3 of GB / T 17519.

Section 4 First Aid Measures	
In case of inhalation:	Immediately remove person to fresh air. If breathing has stopped, give artificial

According to GB/T 16483-2008 and GB/T 17519-2013 Sea Foam High Mileage

	Sea Foarn Fight Mileage
Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022	SDS Record Number: CSSS-TCO-010-151567
	respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
In case of skin contact:	Immediately remove/take off all contaminated clothing. Wash exposed area thoroughly with soap and water for at least 15 minutes. If irritation or symptoms develop, seek medical attention.
In case of eyes contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
In case of ingestion:	Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
Most important symptoms and effects, both	Causes serious eye irritation. May cause drowsiness and dizziness.
acute and delayed:	May be fatal if swallowed and enters airways.
To protect playing rescuer advice and the	Ensure that medical personnel are aware of the material(s) involved, and take
special hints to the doctor:	precautions to protect themselves.
Indication of any immediate medical attention	Provide general supportive measures and treat symptomatically. In the event of
and special treatment needed:	shortness of breath, give oxygen. Keep the victim warm. Observe the patient. Symptoms may delay.

Section 5 Fire-fighting Measures	
Extinguishing agent	
Suitable extinguishing media:	Dry chemical, foam, carbon dioxide and water fog.
Unsuitable extinguishing media:	Do not use a solid water stream as it may scatter and spread fire.
Special hazards:	Flammable liquid and vapor. May be ignited by open flame. Vapors are heavier
	than Air and collect in confined and low-lying areas. The product is insoluble and
	floats on water. The pressure in sealed containers can increase under the
	influence of heat. Hazardous combustion products: Carbon oxides; Nitrogen
	oxides (NOx); Sulphur oxides; Other unidentified organic compounds; irritating
	fumes and smoke.
Special fire fighting methods and special	Firefighters should wear self-contained breathing apparatus, and wear full body
protective actions for fire-fighters:	fire service and extinguish fire in the windward direction. Remove the container
	from the fire to empty place as far as possible. Cool the container exposed to the
	fire with water and vent the vapors. Isolate the accident area, prohibit access to
	unrelated persons. Contain and handle fire water to prevent environmental
	pollution.

Section 6 Accidental Release Measures

Personal precautions, protective equipment	All persons dealing with clean-up should wear the appropriate protective
and emergency procedures:	equipment including self-contained breathing apparatus. Keep all other personnel
	upwind and away from the spill/release. Restrict access to area until completion
	of clean-up. Refer to protective measures listed in sections 7 and 8.
Environmental precautions:	Avoid release to the environment. In case of leakage into drainage system /
	aquatic environment, notify local authorities. Take measures to prevent further
	releases or spills while ensuring safety. Prevent spills from entering water, sewer,
	basement or limited space.
Methods and materials for containment and	Ventilate the area. Remove all sources of ignition. Prevent further leakage or

According to GB/T 16483-2008 and GB/T 17519-2013 Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022	SDS Record Number: CSSS-TCO-010-151567
cleaning up:	spillage if safe to do so. Use only non-sparking tools. Soak up with inert absorbent material. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities
Precautions to prevent the occurrence of secondary hazards:	Clean up spills immediately to prevent leaks again.

Section 7 Handling and Storage	
Safe handling	
Local and general ventilation:	Provide adequate ventilation.
Safety instructions:	Operators should follow the procedure and use the personal protective equipment recommended by the SDS section 8.
Precautions:	Keep away from open flames, hot surfaces and sources of ignition. In case of poor ventilation wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Wash hands thoroughly after handling and prohibit eating in the workplace. Handling products should be carefully unloading, to avoid damage to packaging and containers.
Storage	
Suitable storage conditions:	Store in a cool, dry, well-ventilated area. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. No smoking. Protect from sunlight. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.
Incompatible materials:	Strong oxidizing agents; Acids; Caustics.
Safe packaging materials:	Keep it in the original container.

Section 8 Exposure Controls / Personal Protection

Occupational exposure limits:	According to GBZ2.1,
	Isopropanol (CAS#67-63-0)
	- PC-TWA=350mg/m ³ 、PC-STEL=700mg/m ³ .
Biological limits:	No standard has been established.
Engineering controls:	Ensure adequate ventilation. Make sure the workplace is equipped with a safe
	place to shower, clean eyes and body, and place for safe care.
Personal protection equipment	
Respiratory protection:	If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised.
Hand protection:	Impervious gloves must be worn when using this product.
Eye protection:	Chemical safety glasses with side shields or splash proof goggles. A full-face
	shield may also be necessary.
Skin and body protection:	Wear long sleeved shirt and pants to minimize exposed skin.
Hygiene measures:	Avoid contact with eyes. Wash hands after handling. Do not eat and drink in the
	workplace.

Section 9 Physical and Chemical Prop	erties
Appearance:	Clear liquid

According to GB/T 16483-2008 and GB/T 17519-2013 Sea Foam High Mileage

Version 1.0
Issue date:20/06/2022
Revision date: 20/06/2022

SDS Record Number:	CSSS-TCO-010-151567

Odor:	Typical odor.
Odor threshold:	No data available
Molecular formula:	Not applicable
Molecular weight:	Not applicable
Melting point/freezing point (°C):	No data available
Boiling point, initial boiling point (°C):	68°C
Density:	No data available
Relative density(H ₂ O=1):	0.819
Vapor pressure (20°C) (kPa):	No data available
Partition coefficient (n-octanol/water):	No data available
Solubility in water:	Insoluble
Solubility in organic solvents:	No data available
Flash point (°C):	24°C
Auto-ignition temperature (°C):	No data available
Flammability limit - lower (%):	No data available
Flammability limit - upper (%):	No data available
Decomposition temperature (°C):	No data available
Flammability (solid, gas):	No data available
Explosive properties	Not explosive
Explosive limit - lower (%):	No data available
Explosive limit - upper (%):	No data available
pH value:	No data available
Viscosity (mPa • S):	No data available
Relative vapor density (air=1):	>1
Relative evaporation rate (n-butyl acetate=1):	<1
VOC	367g/l

Section 10 Stability and Reactivity

Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	No dangerous reaction known under conditions of normal use.	
Conditions to avoid:	Avoid heat and open flame. Do not use in areas without adequate ventilation.	
	Avoid contact with incompatible materials.	
Incompatible materials:	Strong oxidizing agents; Acids; Caustics.	
Hazardous decomposition products:	Carbon oxides; Nitrogen oxides (NOx); Sulphur oxides; Other unidentified	
	organic compounds; irritating fumes and smoke.	

Section 11 Toxicological Information	
Acute toxicity	
Isopropanol (CAS#67-63-0)	
LD50(Oral, Rat):	5.84 g/kg
LD50(Dermal, Rabbit):	16.4 mL/kg bw
LC50(Inhalation, Rat):	Not available
Skin corrosion/Irritation:	Not classified
Serious eye damage/irritation:	Causes serious eye irritation.
Respiratory or skin sensitization:	Not classified

According to GB/T 16483-2008 and GB/T 17519-2013

Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022

SDS Record Number: CSSS-TCO-010-151567

Germ cell mutagenicity:	Not classified
Carcinogenicity:	Not classified
Reproductive toxicity:	Not classified
STOT- single exposure:	May cause drowsiness and dizziness.
STOT-repeated exposure:	Not classified
Aspiration hazard:	May be fatal if swallowed and enters airways.

Section 12 Ecological Information

Ecotoxicity	
Isopropanol (CAS#67-63-0)	
LC50 (Fish, 96h)	10 000 mg/L
EC50 (Daphnia, 48h)	Not available
EC50 (Algae, 72h):	Not available
Persistence and degradability:	No data available
Bioaccumulative potential:	No data available
Mobility in soil:	No data available

Section 13 Disposal Considerati	ons
Residual waste	Recycling as much as possible. If recycling is not possible, use incineration
	methods for disposal. Do not dispose of this product by means of discharge to the
	sewer.
Contaminated packaging	Empty containers or pads may retain some product residue, so beware of label
	warnings even when empty containers. These materials and their containers
	must be disposed of in a safe manner. Empty containers should be returned to
	the manufacturer or sent to a national / local approved waste disposal site.
Local disposal regulations	Waste disposal should refer to the relevant national and local laws and
	regulations, the waste chemicals for recycling, or packed in sealed containers, to
	a special waste disposal sites.

Section 14 Transport Information	
UN Number:	UN1993
UN Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Hydrocarbon blend, Isopropanol)
Transport hazard Class:	3
Packaging group:	III
Marine pollutant (yes/no):	No

Transport special precautions:

- Grounding chains should be equipped with tank or car during transportation, hole plate can be set in the tank to prevent static electricity generated by shaking;

- Exhaust pipe of the vehicle which transports this product shall be equipped with fireproofing equipment, Do not handle with the machinery or tools which may produce spark easily;

Do not package or transport with oxidant, food chemicals or others;

Prevent from sunlight exposure, rain and heat during transportation, in summer, best to transport in the morning or evening;

According to GB/T 16483-2008 and GB/T 17519-2013

Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022

SDS Record Number: CSSS-TCO-010-151567

- Keep away from fire, heat source and high temperature when stops on the way;
- Follow the route as prescribed during highway transportation, do not stay in residential areas and densely populated area;
- Prohibit humping in railway transportation;
- Transport vehicles should be equipped with corresponding fire equipment and spill contingency processing equipment.

15.Regulatory Information

The following laws, regulations, rules and standards, provide corresponding provisions of the management of chemicals:

Name	Relevant Inventories	Listed Or Not
Magguros On Safaty Management Of	Inventory Of Hazardous Chemicals	Listed
Measures On Safety Management Of Hazardous Chemicals	The First Batch Of Key Regulatory List Of	Isopropanol not listed, others unknown
Tiazardous Chemicais	Hazardous Chemicals	isoproparior not listed, others driknown
Measures On New Substance	The Inventory Of Existing Chemical	leapropagal listed, others upknown
Environmental Management	Substance In China	Isopropanol listed, others unknown
Provisions On Environmental Management	China Strictly Restricted List Of Import And	Isopropanol not listed, others unknown
Of First Import And Export Of Toxic	Export Of Toxic Chemicals	
Chemicals		

Section 16 Other Information

Indication of changes:

Version 1.0 Amended by GB/T16483 and GB/T 17519.

Abbreviations:

CAS: Chemical Abstracts Service

LC50: Lethal Concentration 50

EC50: Concentration for 50% of maximal effect

LD50: Lethal dose 50%

PC-TWA: time-weighted average allowable concentration, average allowable concentration in 8h working day, 40h work week.

PC-STEL: Short-Term Exposure Tolerance, the concentration allowed to be exposed in short-term (15 minutes).

IARC: International Agency for Research on Cancer

ACGIH: US Government Conference of Industrial Hygienists

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Dangerous Goods

EINECS: European Inventory of Existing commercial Chemical Substances

IATA: International Air Transport Association

ICAO-TI: International Civil Aviation Organization The International Civil Aviation Covenant

Disclaimer:

The information in this Safety Data Sheet (SDS) applies only to the products specified and does not apply to mixtures containing this product with other substances, unless otherwise specified. This Safety Data Sheet (SDS) is based on information currently available in all its aspects and will not be held responsible for its long-term timeliness. This Safety Data Sheet (SDS) provides information about the safety of the product for the intended purpose only to appropriately trained personnel operating the product. Users of this SDS must make independent judgments on the suitability of this SDS for special conditions of use, the SDS author will not be responsible for the damage caused by the use of this Safety Data Sheet (SDS). Each user of the product should read carefully the contents of this Safety Data Sheet (SDS) before proceeding. For more information to ensure correct evaluation, please contact the product supplier.

Author: Hangzhou REACH Technology Group Co., Ltd. Tel:86-571-87206555

Email: info@cirs-group.com

According to GB/T 16483-2008 and GB/T 17519-2013 Sea Foam High Mileage

Version 1.0 Issue date:20/06/2022 Revision date: 20/06/2022

SDS Record Number: CSSS-TCO-010-151567