



SEA FOAM SPRAY SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 1 of 9

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : Sea Foam Spray
Product code : SS14INT
Product form : Mixture
Vaporizer : Aerosol
Relevant Identified uses : Intended for general public.
Main use category : Industrial use, consumer use.
Use of substance/mixture : Engine treatment/cleaner.
 Internal engine use only.
Uses advised against : No additional informational available.
Manufacturer : **Sea Foam International, Inc.**
 812 Burlington Drive, Suite 100
 Bismarck, ND 58504-0639
 T (701) 751-7363
Distributor : **C M Frost**
 Unit 6 Everitt Close Denington Industrial Estate
 Northamptonshire Wellingborough
 NN8 2QE United Kingdom
 T 0044 (0) 1933 225 564
customerservice@topspeedautomotive.com
Emergency telephone number : INFOTRAC : 1 (352) 323-3500 (International)
 1-800-535-5053 (US & Canada)
Country **Great Britain** **Emergency Number**
 National Poisons Information Service 0344 892 0111
 (Birmingham Centre) City Hospital
 Dudley Road
 B18 7QH Birmingham



SECTION 2. HAZARDS IDENTIFICATION

Classification according to Regulation (EC) No. 1272/2008 [CLP]

CLP Classification

Aerosol 1	H222; H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes and H-statements: See section 16.

Adverse physiochemical, human health, and environmental effects: No additional information available.

Label according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02



GHS07



GHS08

Signal Word (CLP)

DANGER

Precautionary statements (CLP)

P101 - If medical advice is needed, have product container or label at hand.
 P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P271 - Use only outdoors or in a well-ventilated area.
 P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
 P405 - Store locked up.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Unknown acute toxicity (CLP)

2.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
 2.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
 56.4% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Unknown hazards to the aquatic environment

Contains 2.8% of components with unknown hazards to the aquatic environment.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 2 of 9

Hazard ingredients

Isopropyl alcohol, Distillates, petroleum, hydrotreated heavy naphthenic, and Naphtha, petroleum, hydrotreated light

Hazard statements (CLP)

H222 - Extremely flammable aerosol.
H229 - Pressurized container: May burst if heated.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Child-resistant fastening

Not applicable.

Tactile warning

Not Applicable.

Other hazards

No additional Information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Name	Product Identifier	% wt	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates, petroleum, hydrotreated heavy naphthenic (Note L)	(CAS-No.) 64742-52-5 (EC-No.) 265-155-0 (EC Index-No.) 649-467-00-8	50-60	Asp. Tox. 1, H304
Naphtha, petroleum, hydrotreated light (Note P)	(CAS-No.) 64742-49-0 (EC-No.) 265-151-9;927-510-4 (EC Index-No.) 649-328-00-1	20 – 30	Flam. Liq. 1, H224 Asp. Tox. 1, H304
Isopropyl alcohol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbon dioxide substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	(CAS-No.) 124-38-9 (EC-No.) 204-696-9	1 – 5	Press. Gas (Comp.), H280

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1% w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-Statements: see section 16.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

<i>First-aid measures after inhalation</i>	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
<i>First-aid measures after skin contact</i>	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
<i>First-aid measures after eye contact</i>	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
<i>First-aid measures after ingestion</i>	: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

<i>Symptoms/effects after inhalation</i>	: May displace oxygen and cause rapid suffocation. May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
<i>Symptoms/effects after skin contact</i>	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
<i>Symptoms/effects after eye contact</i>	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 3 of 9

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia.

Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Dry chemical. Alcohol foam. Carbon dioxide (CO₂). Water fog.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Products of combustion may include and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. Will float and can be reignited on water surface.

Explosion hazard : Heavier than air, vapours may travel long distances along ground, ignite and flash back to source. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.

Protection during firefighting : Keep upwind of fire. Wear full firefighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges. Isolate from fire, if possible, without unnecessary risk.

For non-emergency personnel : No additional information available.

For emergency responders : No additional information available.

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.

Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so. Eliminate every possible source of ignition. Do not use sawdust or other combustible material to absorb spilled material. Absorb and/or contain spill with inert material (sand, vermiculite, or other appropriate material), then place in a suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

Reference for other sections : For further information see section 8: "Exposure controls/personal protection".

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling :

Additional Hazards when processed : Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 4 of 9

Hygiene measures : Take off contaminated clothing and wash it before reuse. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Protect from sunlight. Store in a well-ventilated place. Store locked up.

Incompatible materials : Strong oxidizing agents. Heat Sources.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Isopropyl alcohol (67-63-0)

United Kingdom

WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm

Carbon dioxide (124-38-9)

EU

IOEL TWA	9000 mg/m ³
IOEL TWA [ppm]	5000 ppm

United Kingdom

WEL TWA (OEL TWA) [1]	9150 mg/m ³
WEL TWA (OEL TWA) [2]	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
WEL STEL (OEL STEL) [ppm]	15000 ppm

Exposure Controls

Appropriate engineering controls : Ensure good ventilation of the work-station.

Hand protection : Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Eye protection : Safety eyewear complying with an approved standard such as the European Standard EN166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink, or smoke when using this product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Liquid.

Flammability (solid, gas):

Extremely flammable aerosol.

Appearance:

Clear liquid. Aerosol.

Vapour pressure:

80 – 90 psig



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 5 of 9

Colour:
Clear.

Odour:
Petroleum. Hydrocarbon.

Odour threshold:
No data available.

pH:
No data available.

Relative evaporation rate (butylacetate=1)
< 1

Melting point:
No data available.

Freezing point:
No data available.

Boiling point:
82.2 °C / 180 °F

Flashpoint:
12.8 °C / 55 °F (Concentrate)

Auto-ignition temperature:
No data available.

Decomposition temperature:
No data available.

Relative vapour density at 20 °C/68 °F:
>1 (heavier than air)

Relative density:
0.8

Solubility:
Slightly soluble. Water: 0.1- < 1.0%.

Partition coefficient n-octanol/water:
No data available.

Partition coefficient n-octanol/water
No data available.

Viscosity, kinematic:
No data available.

Viscosity, dynamic:
No data available.

Explosive properties:
Not explosive.

Oxidising properties:
No data available.

Explosive limits:
No data available.

Other Information:
VOC Content : 367 g/l
Gas group : Compressed gas
Flame projection : >100 cm
Heat of Combustion : 34 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials. Sparks. Open flames. Direct sunlight. Overheating. Sources of ignition.
Incompatible materials	: Strong oxidizing agents. Strong acids. Strong bases.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. May release flammable gases.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects	
<i>Acute toxicity (oral)</i>	: Not classified.
<i>Acute toxicity (dermal)</i>	: Not classified.
<i>Acute toxicity (inhalation)</i>	: Not classified.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 6 of 9

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	73680 ppm/4h

Isopropyl alcohol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat	72600 mg/m ³ (Exposure time: 4 h)

Unknown acute toxicity (CLP)	: 2.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 2.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 56.4% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
<i>Additional Information</i>	: Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity	: Not classified.
<i>Additional Information</i>	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified.
<i>Additional information</i>	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Not classified.
<i>Additional information</i>	: Based on available data, the classification criteria are not met.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
<i>Additional information</i>	: Based on available data, the classification criteria are not met.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

Sea Foam Spray	
Vaporizer	Aerosol

Other information : Likely routes of exposure: ingestion, inhalation, skin, and eye.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

<i>Ecology – general</i>	: May cause long-term adverse effects in the aquatic environment.
<i>Unknown hazards to the aquatic environment (CLP)</i>	: Contains 2.8% of components with unknown hazards to the aquatic environment.
<i>Hazardous to the aquatic</i>	: Not classified.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 7 of 9

environment, short-term (acute)

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Naphtha, petroleum, hydrotreated light (64742-49-0)	
LC50 - Fish [1]	8.41 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static, closed])
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	12.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	18.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Isopropyl alcohol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)

Persistence and degradability

Sea Foam Spray : Not established.

Bioaccumulative potential

Sea Foam Spray : Not established.

Isopropyl alcohol (67-63-0) : Partition coefficient n-octanol/water : 0.05 (at 25 °C / 77 °F)

Carbon dioxide (124-38-9) : BCF - Fish [1] : No bioaccumulation.

Mobility in soil : No additional information available.

Results of PBT and vPvB assessment : No additional information available.

Other adverse effects

Additional information : No other effects known.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Product/packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

Additional information : Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of explosion.

SECTION 14. TRANSPORTATION INFORMATION

In accordance with ADR / IMDG / IATA

UN number

UN-No. (ADR) : 1950

UN-No. (IMDG) : 1950

UN-No. (IATA) : 1950

UN proper shipping name

Proper shipping name (ADR) : AEROSOLS (Limited Quantity)

Proper shipping name (IMDG) : AEROSOLS (LTD QTY)

Proper shipping name (IATA) : Aerosols, flammable (Limited Quantity)

EN (English)



SEA FOAM SPRAY SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758


Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 8 of 9

Transport hazard class(es)


ADR

Transport hazard class(es) (ADR) : Limited Quantity

Danger labels (ADR) : 

IMDG

Transport hazard class(es) (IMDG) : Limited Quantity

Danger labels (IMDG) : 2.1
: 

IATA

Transport hazard class(es) (IMDG) : 2.1, Limited quantity for air transport

Danger labels (IMDG) : 2.1
:  

Packaging group

Packing group (ADR) : Not applicable.

Packing group (IMDG) : Not applicable.

Packing group (IATA) : Not applicable.

Environmental hazards

Dangerous for the environment : No.

Marine pollutant : No.

Other information : No supplementary information available.

Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Overland transport : No data available.

Transport by sea : No data available.

Air transport : No data available.

Transport in bulk according to Annex II of
MARPOL 73/78 and the IBC Code : Not applicable.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific to substance or mixture

EU Regulations

: Contains no REACH substances with Annex XVII restrictions.
: Contains no REACH candidate substance.
: Contains no REACH Annex XIV substances.
: Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
: Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 367g/l

National regulations : No additional information available.

Chemical safety assessment : No chemical safety assessment has been carried out.



SEA FOAM SPRAY

SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,
as amended by UK REACH Regulations SI 2019/758

Version: 4022UK
SDS Revision Date: 13/02/2023

Applicable Law: United Kingdom
Page 9 of 9

SECTION 16. OTHER INFORMATION

Indication of changes	: None.
Data Sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.
Full text of H- and EUH-statements	
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification and procedure used to derive the classifications for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	Calculation Method
Skin Irrit. 2	H315	Calculation Method
Eye Irrit. 2	H319	Calculation Method
STOT SE 3	H336	Calculation Method
Asp. Tox. 1	H304	Calculation Method

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.