



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 1 of 9

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product name** : Sea Foam Deep Creep  
**Product code** : DC14INT  
**Product form** : Mixture  
**Vaporizer** : Aerosol  
**Relevant identified uses** : Intended for the general public.  
**Main use category** : Industrial use, consumer use.  
**Use of substance/mixture** : Lubricating and penetrating oil.  
**Uses advised against** : No additional information available.  
**Manufacturer** : **Sea Foam International, Inc.**  
P.O. Box 639  
Bismarck, ND 58502-0639  
T (701) 751-7363  
**Distributor** : **C M Frost**  
Unit 6 Everitt Close Denington Industrial Estate  
Northamptonshire Wellingborough  
NN8 2QE United Kingdom  
T 0044 (0) 1933 225 564  
[customerservice@topspeedautomotive.com](mailto:customerservice@topspeedautomotive.com)  
**Emergency Telephone Number** : INFOTRAC : 1 (352) 323-3500 (International)  
1-800-535-5053 (US & Canada)  
**Country** **Great Britain** **Emergency Number**  
National Poisons Information Service 0344 892 0111  
(Birmingham Centre) City Hospital  
Dudley Road  
B18 7QH Birmingham



## SECTION 2. HAZARDS IDENTIFICATION

Classification according to Regulation (EC) No. 1272/2008 [CLP]

### CLP Classification

Aerosol 1 H222; H229  
Asp. Tox. 1 H304

Full text of hazard classes and H-statements: See section 16.

**Adverse physiochemical, human health, and environmental effects:** No additional information available.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### Hazard pictograms (CLP)



GHS02

GHS08

### Signal Word (CLP)

DANGER

### Hazard statements (CLP)

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H304 - May be fatal if swallowed and enters airways.

### Precautionary statements (CLP)

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames,

### Precautionary statements (CLP), continued

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national, and/or international regulation.

### EUH statements

EUH 208 - Contains Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts, Benzenesulfonic acid, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

### Unknown acute toxicity (CLP)

2.68% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
43.55% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
72.9% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

### Unknown hazards to the aquatic environment

Contains 44.25 % of components with unknown hazards to the aquatic environment.

### Child-resistant fastening

Not applicable.

### Tactile warning

Not applicable.

### Other hazards



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 2 of 9

and other ignition sources. No smoking.

May displace oxygen and cause rapid suffocation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

Name	Product Identifier	% wt	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Paraffin oils (petroleum), catalytic dewaxed light (Note L)	(CAS-No.) 64742-71-8 (EC-No.) 265-176-5 (EC Index-No.) 649-478-00-8	25 – 45	Asp. Tox. 1, H304
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8 (EC-No.) 265-149-8;926-141-6 (EC Index-No.) 649-422-00-2	25 – 35	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Distillates, petroleum, hydrotreated heavy paraffinic (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8	10 – 30	Asp. Tox. 1, H304
Isopropyl alcohol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbon dioxide substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	(CAS-No.) 124-38-9 (EC-No.) 204-696-9	1 – 5	Press. Gas (Comp.), H280
Benzenesulfonic acid, di-C10-14-alkyl derivatives, calcium salts	(CAS-No.) 1471316-72-9 (EC-No.) 939-603-7	0,1 – 1	Skin Sens. 1B, H317
Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts	(CAS-No.) Not available (EC-No.) 947-519-7 (EC Index-No.) 947-519-7	< 0,2	Skin Sens. 1B, H317

**\*Note L :** The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-Statements: see section 16

## SECTION 4. FIRST-AID MEASURES

### Description of first aid measures

- First-aid measures after inhalation* : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact* : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion* : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation* : May displace oxygen and cause rapid suffocation. May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact* : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact* : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking, and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion* : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

### Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment* : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing media

- Suitable extinguishing media* : Dry chemical. Alcohol foam. Carbon dioxide (CO<sub>2</sub>). Water fog.
- Unsuitable extinguishing media* : Do not use a solid water stream as it may scatter and spread fire.

### Special hazards arising from the substance or mixture



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 3 of 9

- Fire hazard* : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. Will float and can be reignited on water surface.
- Explosion hazard* : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

#### Advice for firefighters

- Firefighting instructions* : Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
- Protection during firefighting* : Keep upwind of fire. Wear full firefighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment, and emergency procedures

- General measures* : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.
- Non-emergency Personnel* : No additional information available.
- Emergency Personnel* : No additional information available.

- Environmental precautions** : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### Methods and materials for containment and cleaning up

- For containment* : Stop leak if safe to do so. Eliminate every possible source of ignition. Do not use sawdust or other combustible material to absorb spilled material. Absorb and/or contain spill with inert material (sand, vermiculite, or other appropriate material), then place in a suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up* : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

- Reference for other sections** : For further information see section 8: "Exposure controls/personal protection".

### SECTION 7. HANDLING AND STORAGE

#### Precautions for safe handling

- Additional hazards when processed* : Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling* : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only in well-ventilated areas. Take precautionary measures against static discharge. Use explosion-proof equipment.
- Hygiene measures* : Wash contaminated clothing before reuse. Always wash hands after handling the product.

#### Conditions for safe storage, including any incompatibilities

- Technical measures* : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions* : Keep out of the reach of children. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Store in a dry, cool and well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Store locked up. Keep in fireproof place.
- Incompatible materials* : Strong oxidizing agents. Acids. Caustics. Heat Sources.

- Specific end use(s)** : Not available.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Control parameters

#### Isopropyl alcohol (67-63-0)

#### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	999 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm

#### Carbon dioxide (124-38-9)



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 4 of 9

## United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	9150 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	15000 ppm

## Exposure Controls

<i>Appropriate engineering controls</i>	: Provide local exhaust or general room ventilation. Provide readily accessible eye wash stations and safety showers. Use explosion-proof equipment.
<i>Hand protection</i>	: Chemical resistant gloves (according to European standard NF EN 374 or equivalent).
<i>Eye protection</i>	: Safety eyewear complying with an approved standard such as the European Standard EN166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts.
<i>Skin and body protection</i>	: Wear suitable protective clothing.
<i>Respiratory protection</i>	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
<i>Environmental exposure controls</i>	: Avoid release to the environment.
<i>Other information</i>	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink, or smoke when using this product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical State:

Liquid.

### Appearance:

Aerosol.

### Colour:

Clear, Colourless.

### Odour:

Petroleum hydrocarbon (solvent).

### Odour threshold:

No data available.

### pH:

No data available.

### Relative evaporation rate (butylacetate=1)

No data available.

### Relative evaporation rate (ether=1)

> 1 (Slower than ether)

### Melting point:

No data available.

### Freezing point:

No data available.

### Boiling point:

82.2°C / 180°F

### Flash point:

12.2°C / 54°F (Concentrate) TCC

### Auto-ignition temperature:

No data available.

### Decomposition temperature:

No data available.

### Flammability (solid, gas):

Extremely flammable aerosol.

### Vapour pressure:

80 – 90 psig.

### Relative vapor density at 20 °C/68 °F:

>1 (Heavier than air)

### Relative density:

0.77 (concentrate)

### Solubility:

Slightly soluble in: Water.

### Partition coefficient n-octanol/water:

No data available.

### Viscosity, dynamic:

No data available.

### Explosive properties:

Not explosive.

### Oxidising properties:

No data available.

### Lower explosive limit (LEL):

2.1 (propellant)

### Upper explosive limit (UEL):

8.5 (propellant)

### Other Information:

Gas group: Compressed gas

## SECTION 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	: No dangerous reactions known under normal conditions of use.
<b>Chemical stability</b>	: Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire, or other sources of ignition.
<b>Possibility of hazardous reactions</b>	: No dangerous reactions known under normal conditions of use.
<b>Conditions to avoid</b>	: Heat. Incompatible materials. Sparks. Open flames. Direct sunlight. Overheating. Sources of ignition.
<b>Incompatible materials</b>	: Strong oxidizing agents. Acids. Caustics.
<b>Hazardous decomposition products</b>	: May include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gasses may be released.



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 5 of 9

---



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 6 of 9

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

Isopropyl alcohol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 15 g/kg
LD50 dermal rabbit	> 5000 mg/kg
Benzenesulfonic acid, di-C10-14-alkyl derivatives, calcium salts (1471316-72-9)	
LD50 oral rat	10000 – 20000 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

**Unknown acute toxicity (CLP)** : 2.68% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
43.55% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
72.9% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

**Skin corrosion/irritation** : Not classified.  
*Additional Information* : Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** : Not classified.  
*Additional Information* : Based on available data, the classification criteria are not met.

**Respiratory or skin sensitization** : Contains Benzenesulfonic acid, di-C10-14-alkyl derivatives, calcium salts, Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts. May produce an allergic reaction.  
*Additional Information* : Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** : Not classified.  
*Additional Information* : Based on available data, the classification criteria are not met.

**Carcinogenicity** : Not classified.  
*Additional Information* : Based on available data, the classification criteria are not met.

**Reproductive toxicity** : Not classified.  
*Additional Information* : Based on available data, the classification criteria are not met.

Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male
<b>STOT-single exposure</b>	: Not classified. <i>Additional Information</i> : Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	: Not classified. <i>Additional Information</i> : Based on available data, the classification criteria are not met.



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 7 of 9

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Benzenesulfonic acid, di-C10-14-alkyl derivatives, calcium salts (1471316-72-9)	
NOAEL (oral, rat, 90 days)	> 500 mg/kg bodyweight Animal: rat, Guideline: other:OECD 415
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>Aspiration hazard</b>	: May be fatal if swallowed and enters airways.
<i>Additional Information</i>	: Based on available data, the classification criteria are not met

Sea Foam Deep Creep	
Vaporizer	Aerosol

**Other information** : Likely routes of exposure: ingestion, inhalation, skin, and eye.

## SECTION 12. ECOLOGICAL INFORMATION

### Toxicity

<i>Ecology – general</i>	: May cause long-term adverse effects in the aquatic environment.
<i>Unknown hazards to the aquatic environment (CLP)</i>	: Contains 44.25% of components with unknown hazards to the aquatic environment.
<i>Hazardous to the aquatic environment, short-term (acute)</i>	: Not classified.
<i>Hazardous to the aquatic environment, long-term (chronic)</i>	: Not classified.

Isopropyl alcohol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

### Persistence and degradability

*Sea Foam Deep Creep* : Not established.

### Bioaccumulative potential

*Sea Foam Deep Creep* : Not established.

*Isopropyl alcohol (67-63-0)* : Partition coefficient n-octanol/water : 0.05 (at 25°C / 77°F)



# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 8 of 9

Carbon dioxide (124-38-9) : BCF - Fish [1] : (no bioaccumulation)  
Petroleum distillates, hydrotreated light (64742-47-8) : BCF - Fish [1] : 61 – 159

Mobility in soil : No additional information available.  
Results of PBT and vPvB assessment : No additional information available.  
Other adverse effects : No other effects known.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Product/packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14. TRANSPORTATION INFORMATION

In accordance with ADR / IMDG / IATA

### UN number

UN-No. (ADR) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### UN proper shipping name

Proper shipping name (ADR) : AEROSOLS (each not exceeding 1L capacity)  
Proper shipping name (IMDG) : AEROSOLS (each not exceeding 1L capacity)  
Proper shipping name (IATA) : Aerosols, flammable (each not exceeding 1L capacity)

### Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 2.1  
Danger labels (ADR) :



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) :



#### IATA

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) :



### Packaging group

Packing group (ADR) : Not applicable.  
Packing group (IMDG) : Not applicable.  
Packing group (IATA) : Not applicable.

### Environmental hazards

Dangerous for the environment : No.  
Marine pollutant : No.  
Other information : No supplementary information available.

### Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.  
Overland transport : No data available.  
Transport by sea : No data available.





# SEA FOAM DEEP CREEP SAFETY DATA SHEET

According to REACH Regulation (EC) No. 1907/2006,  
as amended by UK REACH Regulations SI 2019/758

Version: 0723UK  
SDS Revision Date: 13/11/2023

Applicable Law: United Kingdom  
Page 9 of 9

Air transport : No data available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
: Not applicable.

## SECTION 15. REGULATORY INFORMATION

Safety, health, and environmental regulations/legislation specific to substance or mixture

**EU Regulations** : Contains no REACH substances with Annex XVII restrictions.  
: Contains no REACH candidate substance.  $\geq 0,1\%$  / SCL  
: Contains no REACH Annex XIV substances.  
: Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.  
: Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

VOC content : Not determined.

**National regulations** : No additional information available.

**Chemical safety assessment** : No chemical safety assessment has been carried out.

## SECTION 16. OTHER INFORMATION

Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with longlasting effects.

Classification and procedure used to derive the classifications for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	Expert judgment (hired third party)
Skin Sens. 1B	H317	Expert judgment (hired third party)
Asp. Tox. 1	H304	Expert judgment (hired third party)

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.