



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 1 of 9

SECTION 1. IDENTIFICATION OF THE HAZARDOUS CHEMICAL OR MIXTURE AND THE SUPPLIER OR MANUFACTURER

Product name : Sea Foam Concentrated Fuel Injector Cleaner
Product code : IC5MX
Product form : Mixture
Recommended use and restrictions : Gasoline additive
Manufacturer : Sea Foam International, Inc.
P.O. Box 639
Bismarck, ND 58504-0639
T (701) 751-7363



Emergency Telephone Number : +INFOTRAC - (800) 535-5053 (Within Continental US) (8:30am-4:30pm, Mon to Fri, CST); +1 (352) 323-3500 (Outside US) NOTE: INFOTRAC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals.

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS MX Classification

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 2	H361
Asp. Tox. 1	H304
Aquatic Acute 2	H401
Aquatic Chronic 3	H412

GHS Label elements, including precautionary statements

GHS MX labelling

Hazard pictograms (GHS MX)



GHS07

GHS08

Signal word (GHS MX)

DANGER

Hazard statements (GHS MX)

H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H361 - Suspected of damaging fertility or the unborn child.

Hazard statements (GHS MX)

H401 - Toxic to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS MX)

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P264 - Wash hands, forearms and face thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Other Hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Name	Product Identifier	%	GHS MX Classification
Distillates, petroleum, hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7	60 - 70	Asp. Tox. 1, H304
Solvent naphtha, petroleum, light aromatic	(CAS-No.) 64742-95-6	5 - 20	Flam. Liq. 1, H224 Acute Tox. 5 (Dermal), H313 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Polyolefin alkyl phenol alkyl amine	(CAS-No.) Proprietary	5 - 10	Skin Irrit. 2, H315
Benzene, 1,2,4-trimethyl	(CAS-No.) 95-63-6	3 - 7	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 2 of 9

			Acute Tox. 5 (Dermal), H313 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,3,5-Trimethylbenzene	(CAS-No.) 108-67-8	1 - 5	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
n-Propylbenzene	(CAS-No.) 103-65-1	< 3	Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	< 3	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 1, H400
2-Ethylhexanol	(CAS-No.) 104-76-7	< 3	Flam. Liq. 4, H227 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401
Isopropylbenzene	(CAS-No.) 98-82-8	< 3	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Benzene, 1-ethyl-2-methyl-	(CAS-No.) 611-14-3	< 3	Flam. Liq. 3, H226 Eye Irrit. 2A, H319 Repr. 2, H361 Aquatic Chronic 2, H411
1,2,3-Trimethylbenzene	(CAS-No.) 526-73-8	< 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

*Chemical ingredient identity and/or concentration information withheld for some or all components present is confidential business information.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- First-aid measures after inhalation* : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact* : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion* : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation* : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact* : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact* : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion* : May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

Immediate medical attention and special treatment, if necessary



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 3 of 9

Other medical advice or treatment : Treat symptomatically. Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

Special hazards arising from the substance or mixture / Conditions of flammability

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Oxides of sulfur. Oxides of nitrogen.

Reactivity : No dangerous reactions known under normal conditions of use.

Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

Environmental precautions

: Avoid release to the environment. Do not flush to sewer or allow to enter waterways. Prevent further leakage or spillage. Keep away from drains, surface and ground-water and soil. Notify authorities if product enters sewers or public waters.

Methods and materials for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Handling temperature

: ≤ 70 °C (158 °F)

Hygiene measures

: Take off contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage temperature : ≤ 40 °C (104 °F)

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a cool, well-ventilated place. Keep container closed when not in use. Keep away from strong oxidizers.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)

Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	655 mg/m ³
Mexico	OEL STEL (ppm)	150 ppm
Mexico	NOM-047-SSA1-2011 (BEI)	2 g/g creatinine Paramater: Methylhippuric acid – Medium:urine

Isopropylbenzene (98-82-8)



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 4 of 9

Mexico	OEL TWA (mg/m ³)	245 mg/m ³
Mexico	OEL TWA (ppm)	50 ppm
Mexico	OEL STEL (mg/m ³)	365 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm

Appropriate engineering controls : Use adequate ventilation to keep oil mist below applicable standard.

Environmental exposure controls : Avoid release to the environment.

Individual protection measures/Personal protective equipment

Hand protection : Neoprene or nitrile rubber gloves. Wear suitable gloves resistant to chemical penetration. Wear insulated gloves when handling hot product.

Eye protection : Wear eye/face protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where mineral oil mists are generated – use full face respirator with organic vapor cartridge. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle in accordance with good industrial hygiene and safety procedures.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid.

Appearance:

Pale yellow liquid.

Color:

No data available.

Odor:

Petroleum.

Odor threshold:

No data available.

pH:

No data available.

Relative evaporation rate (butylacetate=1)

0

Melting point:

No data available.

Freezing point:

No data available.

Boiling point:

No data available.

Flash point:

> 93 °C / 199 °F (estimated based upon components)

Auto-ignition temperature:

No data available.

Flammability (solid, gas):

No data available.

Vapor pressure:

0.0017 kPa @ 25 °C/68 °F (.013 torr @ 25 °C/68 °F)

Relative vapor density at 20 °C / 68 °F:

No data available

Relative density:

No data available.

Solubility:

Insoluble in water, alcohols. Soluble in organic solvents.

Partition coefficient n-octanol/water:

No data available.

Log Kow

No data available.

Viscosity

No data available.

Viscosity, kinematic:

≈ 20 mm²/s @ 40 °C

Viscosity, dynamic:

No data available.

Explosive properties:

No data available.

Oxidising properties:

No data available.



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 5 of 9

Decomposition temperature:
No data available.

Explosive limits:
No data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Keep away from heat and open flame. Incompatible materials.
Incompatible materials	: Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Smokes. Oxides of sulfur. Oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.
Information on toxicological effects	
<i>Acute toxicity (oral)</i>	: Not classified.
<i>Acute toxicity (dermal)</i>	: Not classified.
<i>Acute toxicity (inhalation)</i>	: Not classified.
<i>Unknown acute toxicity (GHS MX)</i>	: 15.01% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 16.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 81.83% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 15 g/kg
LD50 dermal rabbit	> 5000 mg/kg

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	3400 ppm/4h
ATE MX (oral)	8400 mg/kg bodyweight
ATE MX (dermal)	2500 mg/kg bodyweight
ATE MX (gases)	3400 ppmv/4h

Benzene, 1,2,4-trimethyl- (95-63-6)

LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m ³ (Exposure time: 4 h)
ATE MX (oral)	3280 mg/kg bodyweight
ATE MX (dermal)	2500 mg/kg bodyweight
ATE MX (gases)	4500 ppmv/4h
ATE MX (vapours)	18 mg/l/4h
ATE MX (dust,mist)	1.5 mg/l/4h

1,3,5-Trimethylbenzene (108-67-8)

LC50 inhalation rat	24 g/m ³ (Exposure time: 4 h)
ATE MX (vapours)	24 mg/l/4h
ATE MX (dust,mist)	24 mg/l/4h

n-Propylbenzene (103-65-1)

LD50 oral rat	6040 mg/kg
---------------	------------



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 6 of 9

LC50 inhalation rat	65000 ppm (Exposure time: 2 h)
ATE MX (oral)	6040 mg/kg bodyweight

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal	1700 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	27.57 mg/l/4h
ATE MX (oral)	3500 mg/kg bodyweight
ATE MX (dermal)	1700 mg/kg bodyweight
ATE MX (gases)	4500 ppmv/4h
ATE MX (vapours)	11 mg/l/4h
ATE MX (dust,mist)	1.5 mg/l/4h

2-Ethylhexanol (104-76-7)	
LD50 oral rat	3730 mg/kg
LD50 dermal rabbit	1980 mg/kg
LC50 inhalation rat	> 227 ppm (Exposure time: 6 h)
ATE MX (oral)	3730 mg/kg bodyweight
ATE MX (dermal)	1980 mg/kg bodyweight
ATE MX (gases)	4500 ppmv/4h
ATE MX (vapours)	11 mg/l/4h
ATE MX (dust,mist)	1.5 mg/l/4h

Isopropylbenzene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 µl/kg
LC50 inhalation rat	> 3577 ppm (Exposure time: 6 h)
ATE MX (oral)	1400 mg/kg bodyweight
ATE MX (dermal)	12300 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.

Sea Foam Concentrated Fuel Injector Cleaner	
Viscosity, kinematic (calculated value) (40 °C)	≈ 20 mm ² /s @ 40 °C



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 7 of 9

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

<i>Ecology – general</i>	: Toxic to aquatic life.
<i>Unknown hazards to the aquatic environment (GHS MX)</i>	: Contains 3.11% of components with unknown hazards to the aquatic environment.
<i>Acute aquatic toxicity</i>	: Toxic to aquatic life.
<i>Chronic aquatic toxicity</i>	: Harmful to aquatic life with long lasting effects.

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Benzene, 1,2,4-trimethyl- (95-63-6)

LC50 fish 1	7.19 - 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Partition coefficient n-octanol/water	3.63

1,3,5-Trimethylbenzene (108-67-8)

LC50 fish 1	3.48 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
-------------	--

n-Propylbenzene (103-65-1)

Partition coefficient n-octanol/water	3.68
---------------------------------------	------

Xylenes (o-, m-, p- isomers) (1330-20-7)

LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
BCF fish 1	0.6 - 15
Partition coefficient n-octanol/water	2.77 - 3.15

2-Ethylhexanol (104-76-7)

LC50 fish 1	32 - 37 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	> 7.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	39 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h algae (1)	11.5 mg/l (Species: Desmodesmus subspicatus)
Partition coefficient n-octanol/water	3.1

Isopropylbenzene (98-82-8)

LC50 fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 1	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h algae (1)	2.6 mg/l (Species: Pseudokirchneriella subcapitata)
BCF fish 1	35.5



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 8 of 9

Partition coefficient n-octanol/water	3.7
---------------------------------------	-----

Persistence and degradability

Sea Foam Concentrated Fuel Injector Cleaner : Not established.

Bioaccumulative potential

Sea Foam Concentrated Fuel Injector Cleaner : Not established.

Benzene, 1,2,4-trimethyl- (95-63-6) : Partition coefficient n-octanol/water : 3.63

n-Propylbenzene (103-65-1) : Partition coefficient n-octanol/water : 3.68

Xylenes (o-, m-, p- isomers) (1330-20-7) : BCF fish 1 : 0.6 – 15
Partition coefficient n-octanol/water : 2.77 – 3.15

2-Ethylhexanol (104-76-7) : Partition coefficient n-octanol/water : 3.1

Isopropylbenzene (98-82-8) : BCF fish 1 : 35.5
Partition coefficient n-octanol/water : 3.7

Mobility in soil

Benzene, 1,2,4-trimethyl- (95-63-6) : Partition coefficient n-octanol/water : 3.63

n-Propylbenzene (103-65-1) : Partition coefficient n-octanol/water : 3.68

Xylenes (o-, m-, p- isomers) (1330-20-7) : Partition coefficient n-octanol/water : 2.77 – 3.15

2-Ethylhexanol (104-76-7) : Partition coefficient n-octanol/water : 3.1

Isopropylbenzene (98-82-8) : Partition coefficient n-octanol/water : 3.7

Other adverse effects

Ozone : Not classified.

Other information : No other effects known.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Empty containers or liners may retain some product residues.

SECTION 14. TRANSPORTATION INFORMATION

In accordance with the Secretariat of Communication and Transportation

UN number : Not regulated for transport.

UN proper shipping name

Proper shipping name (UN RTDG) : Not applicable.

Proper shipping name (IMDG) : Not applicable.

Proper shipping name (IATA) : Not applicable.

Transport hazard class(es)

UN RTDG

Transport hazard class(es) (UN RTDG) : Not applicable.

IMDG

Transport hazard class(es) (IMDG) : Not applicable.

IATA

Transport hazard class(es) (IATA) : Not applicable.

Packing group

Packing group (UN RTDG) : Not applicable.



SEA FOAM CONCENTRATED FUEL INJECTOR CLEANER SAFETY DATA SHEET

Version: 4022MX
SDS Revision Date: 26/03/2024

According to the NOM-018-STPS-2015

Applicable Law: Mexico
Page 9 of 9

Packing group (IMDG) : Not applicable.

Packing group (IATA) : Not applicable.

Environmental hazards

Other information : No supplementary information available.

Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15. REGULATORY INFORMATION

No additional information available.

SECTION 16. OTHER INFORMATION INCLUDING INFORMATION RELATING TO THE PREPARATION AND UPDATING OF SAFETY DATA SHEETS

The information is believed to be correct but is not exhaustive and is to be used for guidance only, which is based on current knowledge of the chemical or mixture and is applicable to the appropriate safety precautions of the product.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.