

SAFETY DATA SHEET

According to the NOM-018-STPS-2015

Applicable Law: Mexico Page 1 of 8

### Version: 4021MX SDS Revision Date: 26/03/2024

SECTION 1. IDENTIFICATION OF T	HE HAZARDOUS CHEMICAL OR MIXTURE AND	THE SUPPLIER OR
MANUFACTURER		
Product name	: Sea Foam Spray	
Product code	: SS14MX	
Product form	: Mixture	a Time Com
Recommended use and restrictions	: Engine treatment/cleaner. Internal engine use only.	And a second and a
Manufacturer	<b>: Sea Foam International, Inc.</b> P.O. Box 639 Bismarck, ND 58504-0639 T (701) 751-7363	
Emergency Telephone Number	: +INFOTRAC - (800) 535-5053 (Within Continental US) (8:30am-4:30pm, Mon to Fri, CST); +1 (352) 323-3500 (Outside US) NOTE: INFOTRAC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals.	
SECTION 2. HAZARDS IDENTIFICA	TION	
Classification of the substance or mixture	Precautionary statements (GHS M.	X)

#### GHS MX Classification

Aerosol 1	H222; H229
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Acute 2	H401

### GHS Label elements, including precautionary statements GHS MX labelling

Hazard pictograms (GHS MX)



### Signal Word (GHS MX) DANGER

#### Hazard statements (GHS MX)

- H222 Extremely flammable aerosol.
- H229 Pressurized container: May burst if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H401 Toxic to aquatic life.

#### Precautionary statements (GHS MX)

P101 - If medical advice is needed, have product container or label at hand.

#### P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and

	1210 Reep away non near, not sundees, spans, open names and
	other ignition sources. No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
	P264 - Wash hands, forearms, and face thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER
	or doctor.
	P331 - Do NOT induce vomiting.
	P302+P352 - IF ON SKIN: Wash with plenty of water.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P304+P340 - IF INHALED: Remove person to fresh air and keep
	comfortable for breathing.
	P312 - Call a POISON CENTER or doctor if you feel unwell.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P403 - Store in a well-ventilated place.
	P405 - Store locked up.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501 - Dispose of contents/container to hazardous or special waste
	collection point, in accordance with local, regional, national and/or
	international regulation.
	Other Hazards
	No data available.
hol	

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ν	/lixtures

Name	Product Identifier	% wt	GHS MX Classification
Petroleum distillates	*	*	Asp. Tox. 1, H304



### SAFETY DATA SHEET

According to the NOM-018-STPS-2015

#### Version: 4021MX SDS Revision Date: 26/03/2024

#### Applicable Law: Mexico Page 2 of 8

Hydrocarbon-based solvent	*	÷	Flam. Liq. 1, H224 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Isopropyl alcohol	(CAS-No.) 67-63-0	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

\*Chemical ingredient identity and/or concentration information withheld for some or all components present is confidential business information.

SECTION 4. FIRST-AID MEASURES			
Description of first aid measures			
First-aid measures after inhalation	: If inhaled and breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.		
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.		
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.		
Most important symptoms and effects, both ac	ute and delayed		
Symptoms/effects after inhalation	: May displace oxygen and cause rapid suffocation. May cause irritation to the respiratory tract. May cause drowsiness or dizziness.		
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.		
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.		
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia.		
Immediate medical attention and special treatme	ent, if necessary		
Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).		
Special protective equipment and precautions fo			
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.		
Protection during firefighting	: Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).		

SECTION 5. FIRE-FIGHTING MEASURES		
Extinguishing media		
Suitable extinguishing media	: Dry chemical. Foam. Carbon dioxide (CO2). Water fog.	
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.	
Special hazards arising from the substance	or mixture / Conditions of flammability	
Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. Will float and can be reignited on water surface.	
Explosion hazard	: Heavier than air, vapors may travel long distances along ground, ignite and flash back to source. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.	
Reactivity	: No dangerous reactions known under normal conditions of use.	

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures



### SEA FOAM SPRAY SAFETY DATA SHEET

According to the NOM-018-STPS-2015

Applicable Law: Mexic Page 3 of
: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use or non-sparking tools. Use special care to avoid static electric charges. Isolate from fire, if possib without unnecessary risk.
: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or pub waters. Avoid release to the environment.
cleaning up
: Stop leak if safe to do so. Eliminate every possible source of ignition. Do not use sawdust or other combustible material to absorb spilled material. Absorb and/or contain spill with inert material (sand, vermiculite, or other appropriate material), then place in a suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.
RAGE
: Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Aver contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swalle Handle and open container with care. When using do not eat, drink or smoke. Do not spray an open flame or other ignition source. Use only outdoors or in a well-ventilated area.
: Take off contaminated clothing and wash it before reuse. Always wash hands after handli the product.
: Do not pierce or burn, even after use. Keep away from sources of ignition – No smokir Hazardous waste due to potential risk of explosion.
ncompatibilities
: Proper grounding procedures to avoid static electricity should be followed.
: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. I smoking. Store in a dry, cool, and well-ventilated place. Store locked up. Keep out of the rea of children. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Prote from sunlight. Store in a well-ventilated place.
: Strong oxidizing agents. Heat sources.
LS / PERSONAL PROTECTION
200 ppm
400 ppm

Appropriate engineering controls

: Ensure good ventilation of the work station.



### SEA FOAM SPRAY SAFETY DATA SHEET

According to the NOM-018-STPS-2015

ersion: 4021MX OS Revision Date: 26/03/2024	Applicable Law: Mexico Page 4 of 4
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink o smoke when using this product.
Individual protection measures/Personal prote	ective equipment
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (fac shield) protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selectio must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
SECTION 9. PHYSICAL AND CHEMIC	
Physical State:	Flammability (solid, gas):
Liquid.	Extremely flammable aerosol.
Appearance:	Vapor pressure:
Clear liquid. Aerosol.	80 – 90 psig.
Color:	Relative vapor density at 20 °C / 68 °F:
Clear.	>1 (heavier than air)
Odor:	Relative density:
Petroleum, Hydrocarbon.	0.8
Odor threshold:	Solubility:
No data available.	Slightly soluble in: Water: 0.1 - < 1.0%.
pH:	Partition coefficient n-octanol/water:
No data available.	No data available.
Relative evaporation rate (butylacetate=1)	Partition coefficient n-octanol/water (Log Kow)
< 1	No data available.
Melting point:	Viscosity, dynamic:
No data available.	No data available.
Freezing point:	Explosive properties:
No data available.	No data available.
Boiling point:	Oxidizing properties:
82.2 °C / 180 °F	No data available.
Flash point:	Explosive limits:
12.8 °C / 55 °F	No data available.
Auto-ignition temperature:	Other Information:
No data available.	VOC content : 367 g/l
	Gas group : Compressed gas
Decomposition temperature:	Flame Projection :>45 cm
No data available.	Heat of combustion : 34 kJ/g

### SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Chemical stability

: No dangerous reactions known under normal conditions of use.

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.



ATE MX (dermal)

### SEA FOAM SPRAY SAFETY DATA SHEET

According to the NOM-018-STPS-2015

rsion: 4021MX S Revision Date: 26/03/2024	Applicable Law: Mexic Page 5 of
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials. Sparks. Open flames. Direct sunlight. Overheating. Sources ignition.
Incompatible materials	: Strong oxidizing agents. Strong acids. Strong bases.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Oth unidentified organic compounds. Toxic and irritating gases may be released. May relea flammable gases.
SECTION 11. TOXICOLOGICAL II	NFORMATION
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.
Information on toxicological effects	
Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.
Petroleum distillates (Trade Secret)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
Hydrocarbon-based solvent (Trade Secret	)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	73680 ppm/4h

Isopropyl alcohol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (OECD Guideline 401)
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat	72600 mg/m³ (Exposure time: 4 h)
ATE MX (oral)	5840 mg/kg bodyweight
ATE MX (dermal)	4059 mg/kg bodyweight
ATE MX (vapors)	72.6 mg/l/4h
ATE MX (dust, mist)	72.6 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.

73680 ppmv/4h

okin conosion/initiation					
Serious eye damage/irritation	: Causes serious eye irritation.				
Respiratory or skin sensitization	: Not classified.				
Germ cell mutagenicity	: Not classified.				
Carcinogenicity	: Not classified.				
Reproductive toxicity	: Not classified.				
STOT-single exposure	: May cause drowsiness or dizziness.				
STOT-repeated exposure	: Not classified.				
Petroleum distillates (Trade Secret)					
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)				

Hydrocarbon-based solvent (Trade Secret)



## SAFETY DATA SHEET

According to the NOM-018-STPS-2015

### Version: 4021MX SDS Revision Date: 26/03/2024

#### Applicable Law: Mexico Page 6 of 8

DS Revision Date: 26/03/2024	Page 6 of 8			
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)			
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90- Day Study)			
Aspiration hazard	: May be fatal if swallowed and enters airways.			
Sea Foam Spray				
Vaporizer	Aerosol			
SECTION 12. ECOLOGICAL INFO	RMATION			
Toxicity				
Ecology - general	: Toxic to aquatic life.			
Unknown hazards to the	: Contains 2.8% of components with unknown hazards to the aquatic environment.			
aquatic environment (GHS MX)				
Hazardous to the aquatic	: Toxic to aquatic life.			
environment, short-term				
(acute)				
Hazardous to the aquatic environment, long-term	: Not classified.			
(chronic)				
Petroleum distillates (Trade Secret)				
. ,	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)			
LC50 - Fish [1]				
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
Hyrdrocarbon-based solvent (Trade Secre	t)			
LC50 - Fish [1]	8.41 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static, closed])			
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna			
EC50 72h - Algae [1]	12.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names:			
EC50 72h - Algae [2]	Raphidocelis subcapitata, Selenastrum capricornutum)   18.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names:			
2000 7211 - Aigae [2]	Raphidocelis subcapitata, Selenastrum capricornutum)			
Isopropyl alcohol (67-63-0)				
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas			
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas			
EC50 - Crustacea [1]	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
EC50 72h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)			
EC50 96h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)			
Partition coefficient n-octanol/water	0.05 (at 25 °C / 77 °F)			
Persistence and degradability				
Sea Foam Spray	: Not established.			
Bioaccumulative potential				
Sea Foam Spray	: Not established.			
Isopropyl alcohol (67-63-0)	: Partition coefficient n-octanol/water : 0.05 (at 25 °C / 77 °F)			
Mobility in soil				
Isopropyl alcohol (67-63-0)	: Partition coefficient n-octanol/water : 0.05 (at 25 °C / 77 °F)			
Other adverse effects				
Ozone	: Not classified.			
Other information	: No other effects known.			

### **SECTION 13. DISPOSAL CONSIDERATIONS**



### SEA FOAM SPRAY SAFETY DATA SHEET

According to the NOM-018-STPS-2015

rsion: 402 S Revisio	on Date: 26/03/2024		Applicable Law: Mexico Page 7 of 8				
	Product/Packaging disposal recommendations	with local, regiona drill or burn even a	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do n drill or burn even after use. Empty containers or liners may retain some product residues. The material and its container must be disposed of in a safe way.				
	Additional information : Flammable vapors may accumulate in the container. Hazardous waste d explosion.						
SECTIO	ON 14. TRANSPORTATION I	NFORMATION					
In accorda	ance with the Secretariat of Communic	cation and Transportation	ו				
UN numb	er						
	UN-No. (NOM/SCT)	: 1950					
	UN-No. (IMDG)	: 1950					
	UN-No. (IATA)	: 1950					
UN prope	er shipping name						
	Proper shipping name (NOM/SCT)	: AEROSOLS (Limited	l Quantity)				
	Proper shipping name (IMDG)	: AEROSOLS (LTD QTY)					
	Proper shipping name (IATA)	: Aerosols, flammable	(Limited Qua	antity)			
Transpor	t hazard class(es)						
NOM			I IMDG				
	Transport hazard class(es) (NOM)	: Limited Quantitiy	_	Transport hazard class(es) (IMDG)	: Limited Quantity		
	Danger labels (NOM/SCT)	: 2		Danger labels (IMDG)	: 2.1		
		:			:		
ΙΑΤΑ		$\bullet$			$\bullet$		
	Transport hazard class(es) (IATA)	: 2.1, Limited quantity	for air transp	ort			
	Danger labels (IATA)	: 2.1					
		Y (*)					
Packagin	a aroup	• •					
J	Packing group (NOM/SCT)	: Not applicable					
	Packing group (IMDG)	: Not applicable					
	Packing group (IATA)	: Not applicable					
Environm	iental hazards						
	Other information	: No supplementary	y information	available.			
Special p	recautions for user						
	Special transport precautions	: Do not handle unti	il all safety p	recautions have been read and unde	erstood.		
-NOM							
	Special provisions (NOM/SCT)	: 63, 190, 277, 327,	, 344				
	Limited quantities (NOM/SCT)	: See SP 277					
	Excepted quantities (NOM/SCT)	: E0					
	Packing instruction (NOM/SCT)	: P003, LP02					
	Special packing provisions	: PP17, PP87, L2					
-IMDG	(NOM/SCT)	: No data available.					
-IATA		: No data available.					

: Not applicable.

Sea foam.

### SAFETY DATA SHEET

According to the NOM-018-STPS-2015

Version: 4021MX SDS Revision Date: 26/03/2024 Applicable Law: Mexico Page 8 of 8

### **SECTION 15. REGULATORY INFORMATION**

No additional information available.

### SECTION 16. OTHER INFORMATION INCLUDING INFORMATION RELATING TO THE PREPARATION AND UPDATING OF SAFETY DATA SHEETS

The information is believed to be correct but is not exhaustive and is to be used for guidance only, which is based on current knowledge of the chemical or mixture and is applicable to the appropriate safety precautions of the product.

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.